




3145 County Hwy G, Rhinelander, WI 54501
Ph. 715-369-5700, www.enterprisewood.com

Hardwood Paneling


Square Edge Profile



Square Edge with Reveal Profile



Bevelled Edge Profile



All Tongue and Groove profiles contain relief cuts on back of piece and are not reversible

Thickness: .750"

Widths/Face Coverage: 2-1/4" , 3" , 4" , 5" , 6" , 7"

- Standard pricing is based on a 3, 4, 5" pattern of equal lineal footages.
- Product available in select widths for an additional charge and pending availability.

Lengths: Random lengths of 12" to 96" minimizes waste.

- Specific Lengths available upon request for an additional charge and pending availability.
- Available end-matched or not end-matched.

Texturing Options: Unsanded, Sanded, Century Sawn, Wire Brushed

Grades: Rustic, Select

- Rustic wood grades contain sound knots and the most color & character variation. There may be small cracks less than 1/8" wide and will not continue through entire piece or compromise integrity of board. Some species may contain "pith" if board was cut closer to the center of tree and will not be considered a defect, but a character trait.
- Select wood grades have very small infrequent tight knots and are more uniform in color & character.

Finish Options: Unfinished, Oil Based Polyurethane, Water Based Polyurethane or Lacquer

- Staining available for an additional charge
- Pre-finished square edge paneling will contain small variations in height piece to piece.

Acclimation: Recommended acclimation period of 2 weeks of proper storage at the job site.

- Keep proper humidity levels in your home or business between 35% to 55%
- It is recommended to measure humidity levels in your home using a hygrometer
- For wider width paneling (typically over 5" planks) it is recommended the product be installed within 30 days of storage at your job site.
- It is not recommended to store your wood flooring for long periods of time before installation to prevent irregular natural changes to your wood such as expansion, contraction, cupping, checking, cracking, etc.. Wood is a natural resource that will act naturally if proper conditions are not maintained.
- Always consider a professional installation service or guide for reference before installing.

Reaction to Environmental Conditions

- Wood is a product of nature and will act naturally. It will expand and contract as it gains and loses moisture. Some gaps between boards during low-humidity seasons are normal and not considered a defect. Maintaining optimum humidity levels of 30 to 55% will minimize these occurrences. Allowing relative humidity levels to fall below 30% can result in structural damage to the floor or paneling such as large gaps, splits in the surface, distortion of the boards and structural failure. Humidity levels above 55% can result in surface warping and structural failure of boards.

Light Exposure:

- Varying changes (patina) can occur when wood is exposed to UV rays from sunlight, florescent, LED, and incandescent bulbs. Window coverings, UV resistant tint, solar screens can minimize but not eliminate this natural occurrence. Certain species are more susceptible to light & development of varying degrees/shades of patina, due to their high content of natural oils.

Maintenance:

- Clean with any product approved for use on wood.